EDDY PUMP CORPORATION

MADE IN USA

Hydraulic Excavator Pump Attachment - 10 Inch

MODEL #
10-Inch EXF 10000 Hydraulic Excavator Attachment

OPERATING LEVELS	
MIN FLOW	1200 GPM
MAX FLOW	5000 GPM
HEAD RANGE	Up to 200 ft
DISCHARGE SIZE	10 inch
SUCTION SIZE	12 inch
SOLIDS HANDLING	Solids up to 9 inches
MAX SPEED	1800 RPM
PERCENT SOLIDS	Up to 40-70% Solids
CU YD MATERIAL HR	300-350

*Typical Attachment Photo. Photos for general guidance. Contact us for further details.

RECOMMENDED SENSORS
Hydraulic Pressure Gauge for pumps and cutter head circuit to operator (0-6000 PSI)
Magnetic Flow meter to maintain stable plug free pipeline flow and maximize production

REQUIRED EQUIPMENT TO OPERATE ATTACHMENT
EDDY Pump circuit requirements from excavator auxiliary power OR from Hydraulic Power Unit 120 GPM at 5000 PSI (500cc motor)
Cutterhead circuit requirements from excavator auxiliary power OR from Hydraulic Power Unit 20-28 GPM at 5000 PSI (2150cc motor)
10” material handling discharge hose and hydraulic lines plumbed out to the end of the boom
Crossover check valve to prevent damage to hydraulic motor and prevent pump rotor from coming off
Minimum excavator carrier weight requirements: 60-94 tons / 54,400-85,000 kg

MAXIMUM LINKAGE CROSS SECTION





STANDARD PIN SIZING

PART #	SIZE
12877	Ø90 MM
06661	Ø100 MM
01042	Ø110 MM

*CUSTOM SIZES AVAILABLE UPON REQUEST

© EDDY Pump Corp. | El Cajon, CA 92021 USA | EddyPump.com | Phone: (619) 258-7020 | info@EddyPump.com

EDDY PUMP CORPORATION

MADE IN USA

EDDY Pump industrial Excavator Dredge Pump Attachments are non-clog pumps designed for high solids industrial pumping applications. Our patented pump technology outperforms all centrifugal, vortex and positive displacement pumps in a variety of the most difficult pumping applications.

Available in alternative power options and pump sizes depending on your application.

Applications

- Mining
- Chemical
- Sand & Agg
- Oil and Gas
- Paper & Pulp
- Fly Ash & Coal Ash

Features and Benefits

- Non-Clog, High Viscosity, High Specific Gravity, High Abrasives, Low pH Pumping Design
- Transport 40-70% Solids
- Ability to pump objects of up to 9-inches in diameter

Fluid Pumped

- Sludge
- Slurry
- Drilling Mud
- Mine Tailings
- Grit
- Sand Mixtures

GENERAL SPECS		
Overall Weight (without optional equipment)	7,500 lbs	3,400 kg



© EDDY Pump Corp. | El Cajon, CA 92021 USA | EddyPump.com | Phone: (619) 258-7020 | info@EddyPump.com

EDDY PUMP CORPORATION

MADE IN USA

OPTIONAL EQUIPMENT TO ENHANCE OPERATION OF DREDGE
Magnetic flow meter
Discharge line pressure gauge (0-150 psi)
“Quick Prime” Valve (requires small 24volt air system)
Pivot mounted Discharge hose carrier (adaptable to most machines)
Recirculation system for pre-mixing applications (requires small 24 volt air system)



STANDARD CUTTER HEAD

SELF-CLEANING HEAD

WATTER JETTING RING

LINER-SAFE WHEELS

EXTENDED CUTTER HEAD

RE-CIRCULATION



AUGER HEAD



MIXER HEADS

© EDDY Pump Corp. | El Cajon, CA 92021 USA | EddyPump.com | Phone: (619) 258-7020 | info@EddyPump.com

EDDY PUMP CORPORATION

MADE IN USA

PUMP CURVE

A pump curve is a graphical representation of a pumps ability to produce flow against a certain head. The science is matching a curve that is accurate for your project, leading to the proper pump selection and best efficiency.
EDDY Pumps are primarily used for high solids, slurry, sludge, and dewatering.

EDDY Pump - 10 Inch HD 10000 Heavy Duty Slurry Pump - Pump Curve



*General pump curve based on water with 1200 RPM motor. Contact us with your specific material for a custom pump curve.

WE PUMP SOLIDS, NOT WATER

CONTACT US

(619) 258-7020

info@EddyPump.com